2011 XL1200C

Two-Tone Option \$ 10,809

Custom Color Option

N/A

MSRP starting at

N/A

Wheel Option

N/A

Security Option

\$ 370

ABS Option

N/A

Security Package (Security and ABS)

N/A

Reverse Option

N/A

Cruise Control Option

N/A

California Emissions

\$ 100

Freight

\$ 305

DIMENSIONS

Length

2,220 mm

Seat Height, Laden

676 mm

Seat Height, Unladen

724 mm

Ground Clearance

112 mm

Rake (steering head) (deg)

29.9

Trail

107 mm

Wheelbase

1,521 mm

Tires, Front Specification

130/90B16 72H

Tires, Rear Specification

150/80B16 77H

Fuel Capacity

17 I

Oil Capacity (w/filter)

2.6 I

Weight, As Shipped

251 kg

Weight, In Running Order

264 kg

Luggage Capacity -Volume

N/A

Luggage Capacity - Weight

N/A

ENGINE

Engine

Air-cooled, Evolution®

Bore

88.9 mm

Stroke

96.8 mm

Displacement

1,200 cc

Compression Ratio

9.7:1

Fuel System

Electronic Sequential Port Fuel Injection (ESPFI)

DRIVETRAIN

Primary Drive

Chain, 57/38 ratio

Gear Ratios (overall) 1st

9.315

Gear Ratios (overall) 2nd

6.653

Gear Ratios (overall) 3rd

4.948

Gear Ratios (overall) 4th

4.102

Gear Ratios (overall) 5th

3.517

Gear Ratios (overall) 6th

N/A

CHASSIS

Exhaust

Chrome, staggered exhaust with slash-cut mufflers

Wheels, Optional Style Type

Black Contrast Cut 5-Spoke Cast Aluminum; Steel Laced; Black Steel Laced

Wheels, Front Type

Chrome, 5-Spoke Cast Aluminum

Wheels, Rear Type

Chrome, 5-Spoke Cast Aluminum

Brakes, Caliper Type

Dual-piston front, single-piston rear

Parking Brake

N/A

PERFORMANCE

Engine Torque Testing Method

J1349

Engine Torque

107 Nm

Engine Torque (rpm)

4,000

Lean Angle, Right (deg.)

26.2

Lean Angle, Left (deg.)

28.3

Fuel Economy: Combined City/Hwy

4.9 I/100 km

ELECTRIC

Lights (as per country regulation), Indicator Lamps High beam, neutral, low oil pressure, turn signals, engine diagnostics, low fuel warning, low battery, security system (optional)

Gauges

Handlebar-mounted electronic speedometer with odometer, time-of-day clock on odometer, dual tripmeter, low fuel warning light, low oil pressure light, engine diagnostics readout. LED indicator lights

1

Prices listed are the Manufacturer's Suggested Retail Prices. Options such as color are available at additional cost. Prices exclude dealer setup, taxes, title and licensing and are subject to change. Dealer prices may vary.

2

Measurement reflects 180 lb. (81.7 kg) operator weight.

3

Recommended 91 octane or higher fuel (R+M)/2.

4

Values shown are nominal. Performance may vary by country and region.

5

Standard and optional fuel systems may vary by country.

6

Estimated from fuel economy tests on a sample motorcycle from the corresponding family conducted by Harley-Davidson under ideal laboratory conditions. Not all motorcycle models undergo fuel economy testing. Fuel economy and mileage may vary among motorcycle models within a family. Your mileage may vary depending on your personal riding habits, weather conditions, trip length, vehicle condition and vehicle configuration and other conditions. Break-in mileage may vary.

7

Standard and optional wheels may vary by country and region.

8

North America security system includes immobilizer; outside North America the security system includes immobilizer and siren.

9

See motorcycle owner's manual for complete details.